

PAT-NO: JP357060717A
DOCUMENT-IDENTIFIER: JP 57060717 A
TITLE: QUARTZ OSCILLATOR UNIT
PUBN-DATE: April 12, 1982

INVENTOR-INFORMATION:

NAME
SHINODA, ISAO

ASSIGNEE-INFORMATION:

NAME	COUNTRY
SEIKO INSTR & ELECTRONICS LTD	N/A

APPL-NO: JP55134856

APPL-DATE: September 26, 1980

INT-CL (IPC): H03H009/10

US-CL-CURRENT: 310/344

ABSTRACT:

PURPOSE: To keep airtightness sufficiently without degrading the characteristics of a quartz oscillator, by providing a metallic layer consisting of Cr and Au layers on the surface and the reverse of the frame of a tuning fork type quartz oscillator and setting the film thickness of Cr and Au to $1,000 \sim 3,000 \text{ \AA}$; and $\geq 3,000 \text{ \AA}$; respectively.

CONSTITUTION: Box-shaped vessels 2a and 2b, which hold a quartz oscillator 1 with frame between them, and sealing solders 3a and 3b which seal them tightly are layered and are heated in a vacuum atmosphere, and sealing solders are melted to seal them tightly. In this case, photoetching technique is adopted for a metallized layer 11a of the frame part of the oscillator 1 and a frame

part 21a of vessels 2a and 2b, and a metallic layer consisting of an Au film having $\geq 3,000 \text{ \AA}$; and a Cr film having $1,000 \sim 3,000 \text{ \AA}$; which is provided as the ground for enhancing the adhesive strength of the Au film is provided as the protection film for this photoetching. Thus, a sufficient airtightness is obtained without degrading the characteristics of the quartz oscillator.

COPYRIGHT: (C)1982,JPO&Japio